# NEEDLE BEARING COMPONENTS, AND METHOD FOR PRODUCING THE COMPONENTS

**Publication number:** JP2002180203
**Publication date:** 2002-06-26
**Inventor:** TANAKA HIROMASA
**Applicant:** NTN TOYO BEARING CO LTD
**Classification:**
**- international:** ***F16C19/44; C21D1/06; C21D6/00; C22C38/00; C22C38/58; F16C33/34; F16C33/62; F16C33/64;*** **F16C19/22; C21D1/06; C21D6/00; C22C38/00; C22C38/58; F16C33/30; F16C33/58; F16C33/62;** (IPC1-7): C22C38/00; C21D1/06; C21D6/00; C22C38/58; F16C19/44; F16C33/34; F16C33/62; F16C33/64
**- European:**
**Application number:** JP20000378512 20001213
**Priority number(s):** JP20000378512 20001213



Abstract of **JP2002180203**

PROBLEM TO BE SOLVED: To provide needle roller bearing components in which a long endurance life can be secured even under atmospheric conditions where sliding contact occurs, and the temperature is made high, and to provide a method for producing the components. SOLUTION: The needle roller bearing components consists of steel at least containing, as alloy elements in the base, by mass, 0.1 to 0.4% C, 0.3 to 3.0% Si, 0.2 to 2.0% Mn, <=0.03% P, <=0.03% S, 0.3 to <2.5% Cr, 0.1 to <2.0% Ni, <=0.050% Al, <=0.003% Ti, <=0.0015% O and <=0.025% N, and the balance Fe with inevitable impurities. The steel is subjected to quenching and tempering treatment after carburizing or carbo-nitriding treatment.